


# JOU JYE ELECTRONIC CO.,LTD TAI SON LIMITED

## Power Supply Code Rule



p.s. there's no rules for these 2 codes

Technic ID Nr. & Case Outer Appearance ID Nr.

- A: standard male connector + I/O switch
- B: male+female connector + I/O switch G=RoHS
- C: male+female connector
- D: singular male connector
- K: 1U male connector + I/O switch
- E: 3.96-3PIN+20PIN
- F: DC metal jack
- e.g. PPGA, TSBA, CBBA, TSSA
- S, T, L: identification code

Fan exterior code: in alphabetical order A.B.C.D...

**Specification:**

- |  |  |
|--|--|
| <p>AA=safety + active PFC AC 115V Only</p> <p>AP= safety + active PFC AC 230V Only</p> <p>AU=safety + active PFC AC 90V~AC 264V</p> <p>PA=safety + passive PFC AC 115V Only</p> <p>PP=safety + passive PFC AC 230V Only</p> <p>PU=safety+passive PFC AC 90V~AC 264V</p> <p>PS=safety+passive PFC+switch between (AC 115V/AC 230V)</p> <p>PV=safety+passive PFC+AC AUTO SW 90V/264V</p> <p>NA=without safety AC 115V Only</p> <p>NB=without safety AC 230V Only</p> <p>NU=without safety AC 90V~AC 264V</p> <p>NS=without safety+switch between(AC 115V/AC230V)</p> <p>NV=without safety+AC AUTO SW 90V/264V</p> <p>CA=CE Only AC 230V+active PFC</p> <p>CE=CE Only AC 90V~AC 264V+active PFC</p> <p>CB=CE Only AC 230V</p> <p>CP=CE Only AC 230V+passive PFC</p> <p>CR=CE Only+switch between(AC 115V/AC 230V)+passive PFC</p> <p>CV=CE Only AC AUTO SW 90V/264V+passive PFC</p> <p>CU=CE Only AC 90V~AC 264V</p> <p>CS=CE Only+switch between(AC 115V/AC230V)</p> <p>TA=safety AC 115V Only</p> <p>TB=safety AC 230V Only</p> <p>TU=safety AC 90V~AC 264V</p> <p>TS=safety+switch between( AC 115V/AC 230V)</p> <p>TD=DC-DC</p> <p>DC=DC 12V</p> <p>DD=DC 19V</p> | <p>A:</p> <p>B: PS2 case \ 12CM fan</p> <p>C: PS2 case \ 14CM fan</p> <p>D: PS2 case \ 12CM+8CM fan</p> <p>E: 1U, no fan</p> <p>F: FLEX</p> <p>G: PS2 case \ 8CM fan</p> <p>H:</p> <p>K:</p> <p>L:</p> <p>M: MICRO</p> <p>N: Open frame</p> <p>P:</p> <p>R: REDOUBLE</p> <p>S: PS2 case \ Double 8CM fan</p> <p>T: TFX 12V</p> <p>U: 1U</p> <p>W: 2U</p> <p>Y:</p> <p>Z: Non-standard case</p> |
|--|--|

maximum output power e.g.: 085=85W, 350=350W, 1K0=1000W, 1K2=1200W...

Header: 2 or 3 letters, e.g. JJ, ST, JSP, SGE, SGP, SL, JJB (B means 80+bronze)...