



MINI-204B BLACK MINI-ITX NAS DESKTOP/WALLMOUNT CHASSIS



NU-204B



NU-204B

MINI-ITX 4G LTE NAS Desktop or Wallmount solution Intel X99 compliant and Intel LGA1150, VIA C series platform recommended

The features of this new Mini-ITX chassis are compliant with 4G LTE or high speed WiFi networks and cloud transmission as well as NAS storage application for enterprises and SOHO purpose. It can support maximum two 2.5" SSD/HDD or one 3.5" hard drive. This chassis is made of very durable and high end SGCC 1.0mm thickness and the optional wall mount bracket can be installed in harsh industrial environment. The Cooling system also equipped with one silent 80x25mm fan (option). It also supports one expansion card via riser card.



NU-204B

Drive bay

- Two 2.5" SSD/HDD bay (one expansion card via riser is available)
- or one 3.5" HDD bay (one expansion card via riser is not available)
- * Equipped with two USB 2.0 ports at front bezel (MINI-204B-USB3 if USB 3.0 installed)
- * SGCC 1.0mm high grade sheet metal works as durable mechanism
- * Support wallmount bracket (option, part# Mini-202B-WALL-BK-B)
- * Support one 80x25mm silent fan (option, fan part# D80SM-12C)
- * Support Mini-ITX MB mounting at 6.7" x 6.7" (170mm x 170mm)
- * One expansion card compatible (max. card depth at 170mm via optional riser card)
- * If expansion card or 3.5" HDD installed, maximum 40mm height CPU cooler available
- * If expansion card or 3.5" HDD not installed, maximum 80mm height CPU cooler available
- * Support standard 1U FlexATX 250W PSU
- * Standard paint: scratch-resistant Black textured at surface of chassis

Chassis dimension

224mm x 88mm x 206mm (W x H x D)

Accessory Pack

- M3 truss x6
- M3 countersunk x8
- #6 black countersunk x4
- #6 truss x4
- #6 countersunk x6

Package

NW 1.52 KG, GW 1.92 KG, 0.60 CUFT

Carton size 31cm x 19cm x 29cm)

Model	Mini-204B	Black Mini-ITX NAS Desktop/Wallmount chassis
Model	MINI-204B-USB3	Black Mini-ITX NAS Desktop/Wallmount chassis (USB 3.0 version)
Option A	ENP-7025	1U FlexATX 250W power supply with PFC (psu size 81.5 x 40.5 x 150/mm)
Option B	Mini-202B-WALL-BK-B	Black wall mount bracket (one pair as a unit, MINI-202B & MINI-203B & MINI-204B all compatible)
Option C	D80SM-12C	80x25mm intake cooling fan (one piece as a unit, can be installed at front bezel)
Option D-1	1U1PCIE4XRC	1U 1PCI-Express 4X right angle riser card
Option D-2	1U1PCIE8XRC	1U 1PCI-Express 8X right angle riser card
Option D-3	1U1PCIE16XRC	1U 1PCI-Express 16X right angle riser card
Option E-1	2U active cooler	2U Intel LGA2011 active CPU cooler Square (max. 80mm height when expansion card & 3.5" HDD not installed)
Option E-2	1U active cooler	1U Intel LGA2011 active CPU cooler (max. 40mm height when expansion card or 3.5" HDD installed)
Option E-3	1U active cooler	1U Intel LGA1150 active CPU cooler (max. 40mm height when expansion card or 3.5" HDD installed)